

## FENDER EQUIPMENT TRAILERS – 6" CHANNEL - MODEL DH

### PROFESSIONAL GRADE

- Treated wood deck
- 82" between fenders
- 6" channel frame • 3" channel cross members. 16" spacing
- 5' swing up ramps with support foot
- 2 5/16 adjustable coupler • 12,000 lb. drop-foot jack
- Heavy duty diamond plate fenders with backs
- Stake pockets and rubrail
- Self-charging break away kit, safety chains, DOT reflective tape, and all rubber mounted LED sealed beam lighting with U.S. made sealed modular harness with 5 year warranty
- Primed, 2 coats of automotive grade acrylic enamel, pin striped

#### 10,000 GVWR

- 5,200 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST225/75R15 load range "D" 8 ply rating RADIAL tires
- 5" channel wrap around tongue with toolbox and lockable lid

#### 12,000 GVWR

- 6,000 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST235/80R16 load range "E" 10 ply rating RADIAL tires
- 6" channel wrap around tongue with toolbox and lockable lid

#### 14,000 GVWR

- 7,000 lb. braking axles with 4 wheel brakes
- Slipper spring suspension
- ST235/80R16 load range "E" 10 ply rating RADIAL tires
- 6" channel wrap around tongue with toolbox and lockable lid



### OPTIONS

- Cleated Dovetail • Spring assist on ramps
- Heavy duty split gate with spring assist
- Third ramp • Replacement ramp
- Diamond plate deck (standard length)
- Spare tire and wheel • Spare Mount
- Upgrade to all steel belted load range "G" tires
- Load range "G" spare tire

AVAILABLE SIZES 16' • 18' • 20'

SIZE	PRICE

- Treated wood deck
- 82" between fenders
- 6" channel frame • 3" channel cross members. 24" spacing
- 5' swing up ramps with support foot
- 2 5/16 adjustable coupler • 7,000 lb. drop-foot jack
- Heavy duty diamond plate fenders with backs
- Stake pockets
- Self-charging break away kit, safety chains, DOT reflective tape, and all rubber mounted sealed beam lighting with conventional wiring with gel filled connectors.
- Primed, 2 coats of automotive grade acrylic enamel, pin striped

### GENERAL DUTY

#### 10,000 GVWR

- 5,200 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST225/75D15 load range "D" 8 ply rating BIAS tires
- 5" channel wrap around tongue

#### 12,000 GVWR

- 6,000 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- 750/16 load range "F" 12 ply rating BIAS tires
- 6" channel wrap around tongue

#### 14,000 GVWR

- 7,000 lb. braking axles with 4 wheel brakes
- Slipper spring suspension
- 235/80R16 load range "E" 10 ply rating RADIAL tires
- 6" channel wrap around tongue



### OPTIONS

- Cleated Dovetail • Spring assist on ramps
- Heavy duty split gate with spring assist
- Third ramp • Replacement ramp
- Diamond plate deck (standard length)
- Spare tire and wheel • Spare Mount
- All steel belted load range "G" tires
- Load range "G" spare tire

### GENERAL DUTY OPTIONS

- Sealed modular wiring harness • LED lighting
- Toolbox and lockable lid • Rubrail
- 16" cross member spacing
- 12,000 lb. drop foot jack
- 15" radial tire upgrade • 16" radial tire upgrade

THESE OPTIONS COMBINED MAKE UP THE PROFESSIONAL GRADE PACKAGE

AVAILABLE SIZES 16' • 18' • 20'

SIZE	PRICE